



How to configure a safe Hotspot Logon

There are two ways to configure a safe Hotspot Logon for the NCP Secure Entry Client and the NCP Secure Enterprise Client - with enabled Wi-Fi-management and disabled Wi-Fi management.

Disabled

1. Start the client monitor and go to *Configuration*. Open the Option *Wi-Fi* and go to the tab *Connection*. In this case the checkbox *Enable Wi-Fi management* needs to be unchecked.
2. Go back to the Client Monitor and open the option *Firewall* under *Configuration*.
3. Check the box for *enable Firewall*.
4. The check in the box for *permit IPsec protocol* must be set.
5. If the Firewall is enabled, this icon  will appear in the client monitor.
6. Go to *Connection* and choose *Hotspot Logon*.

Enabled

1. Start the client monitor and go to *Configuration*. Open the Option *Wi-Fi* and go to the tab *Connection*. In this case the checkbox *Enable Wi-Fi management* needs to be checked.
2. Go back to the Client Monitor and open the option *Firewall* under *Configuration*.
3. Check the box for *enable Firewall*.
4. The check in the box for *permit IPsec protocol* must be set.
5. If the Firewall is enabled, this icon  will appear in the client monitor.
6. Everytime when Wi-Fi is available you will receive a notification in the Client Monitor.